



Armaflex® Accessories

► Accessories®



ESSENTIAL TOOLS FOR PROFESSIONAL INSULATION

ARMAFLEX® ACCESSORIES – High quality tools for correct installation of Armaflex products in the air-conditioning, heating, plumbing, and refrigeration industries.



Technical data - Adhesive

Armaflex 520:	General purpose, quick drying adhesive for the joining of Armaflex pipe and sheet insulation. When applied to clean prepared surfaces, and fully cured, it maintains a high-resistance to water vapour.
Armaflex 520 Low VOC:	Designed to meet the latest environmental regulations for the construction of "Green Buildings", this product is low-VOC and both toluene-free and hexane-free. This air-drying contact adhesive is excellent for the joining of seams and butt joints in Armaflex pipe and sheet insulation.
Armaflex 625 (High Temp.):	Designed specifically for use with Armaflex HT insulation, this is suitable for the joining of seams and butt joints where the insulation is used on surfaces up to 150°C.

Properties	Armaflex 520	Armaflex 520 Low VOC	Armaflex 625
Colour	Yellow	Black	Yellow
Coverage	5 - 6m ² / L	5 - 6m ² / L	5 - 6m ² / L
Clean Up	Most lacquer thinners, do not thin	Most lacquer thinners, do not thin	Most lacquer thinners, do not thin
Temperature limits			
- pipe seams and joins	120°C	120°C	150°C
- fully bonded sheet	82°C	82°C	150°C



Armaflex® Adhesive

Description	Carton Content	Product Code
Armaflex 520 Adhesive, 500ml	12 units	9Z000351
Armaflex 520 Adhesive, 1-litre	12 units	9Z000252
Armaflex 520 Adhesive, 5-litre	4 units	9Z000261
Armaflex 520 low VOC Adhesive, 500ml	12 units	9Z000213
Armaflex 625 High Temp Adhesive, 500ml	12 units	9Z000651
Glumaster, adhesive applicator	N/A	9Y000035

Technical data - Tape

Armaflex Self Adhesive Tape:	Self-adhering tape that provides a fast and easy method of insulating fittings, joins and awkward shapes. Manufactured from 3mm thick Armaflex insulation, it is fibre-free and dust-free, and is manufactured without CFCs.
------------------------------	--

Properties	Value/Assesment
Range of application:	
Max. temperature	+ 85°C
Min. temperature	- 40°C
Thermal conductivity at 23°C	0.038 W/(m.k)
Water vapour resistance	μ ≥ 2,500



Armaflex® Tape

Description	Carton Content	Product Code
FR Tape 3mm x 50mm x 9m, grey	12 units	9M000095
AR Tape 3mm x 50mm x 9m, black	12 units	9L000303