

NEW

ROREC PRO Digital

Lightweight recovery unit for the recovery of refrigerants of the classes A1, A2L and A2 (incl. R32). Suitable for all unit sizes thanks to its high recovery rate. Future-proof product for the increased use of R32 refrigerants

6

ROTHENBERGER



+ Safe handling

-

with many refrigerants: Suitable for refrigerants of the classes A1, A2L and A2 (incl. R32)

Light Compact design with a weight of less than 12 kg



rothenberger.com.au

NEWS ROREC PRO Digital





ROREC PRO Digital

Lightweight recovery unit for the recovery of refrigerants of the classes A1, A2L and A2 (incl. R32). Suitable for all unit sizes thanks to its high recovery rate.

- Suitable for refrigerants of the classes A1, A2L and A2 (incl. R32) •
- Compact design with a weight of less than 12 kg •
- Digital display and one-knob control ٠
- Maintenance free operation with the oil-free 2-piston compressor
- 4-pole motor guarantees the durability of the machine ٠
- Automatic shut-off and automatic restart once the • pressure increases again
- Emptying of refrigerant residues with the PURGE function

HENBERG 230 400

HENBERG

pipetool technologies at work

Technical Data

Description	
Recovery Rate	gaseous: 0.5 kg/min; 30 kg/h
	liquid: 3.5 kg/min; 210 kg/h
	Push/Pull: 9.5 kg/min; 570 kg/h
Power supply	230 V / 50 – 60 Hz
Power	730 W
High Pressure Switch	38.5 bar
Product dimensions	38 x 25 x 35 cm
Weight	12 kg

Variants

Model

Wouci	
ROREC PRO	Digital

ROT

		No.
jital	12.0	1500002637



Clearly structured digital display



Practical storage compartment for accessories in the back



Shoulder strap for transport over longer distances





Pressure Hose 3-piece Set

1/4" and 5/16" SAE, 150 cm



ROCOOL 600

Set with 2 temperature sensors For commissioning, maintenance work and documentation of refrigeration systems



No. 1000000570

R32

Analogue Manifolds

2-way and 4-way 1/4" and 5/16" SAE

R32



No. 1000050071 No. 1000050075 No. 1000050073

for ROREC/ROREC PRO Digital

No. 1000050077

Filter

2-way only 4-way only 2-way + hoses 4-way + hoses

ROSCALE 120

Precise refrigerant scale for filling and evacuation processes, max. weight capacity of 120 kg



No. R173004

ROAIRVAC R32 6.0

Two-stage rotary vane pump for evacuation in accordance with **DIN 8975**



No. 1500050007

No. R168713

ROTHENBERGER Australia 6/13 Hoyle Avenue Castle Hill, NSW, 2154

6 02 9899 7577 02 9899 7677 ≤ sales-au@rothenberger.com 🔍 rothenberger.com.au



