



Product Guide

REFCO HVAC-R products are designed
in Switzerland for unparalleled
durability and reliability.

REFMATE

Made for you.

REFMATE is REFCO's new digital manifold that allows you to customise key features, so you can work faster and smarter than ever before.



- 3431010: REFMATE 2 CA
- 3431012: REFMATE 2 CA with Wireless Temp Clamps
- 3431014: REFMATE 4 CA
- 3431016: REFMATE 4 CA with Wireless Temp Clamps

REFMATE at a glance

- 1 Make it yours.** Customise the dials, change your measurement units (bar, psi, MPa, kPa or kg/cm²), and work faster by setting your preferred refrigerants.
- 2 Highly precise.** Swiss accuracy and automatic calculations mean no guesswork or manual computation.
- 3 Lock it and leave it.** Leave connected and wirelessly log data for long-term remote readings.
- 4 Future proof.** Use REFMATE for every job. Easily update with new refrigerants as they become available.
- 5 Fully connected.** The REFMesh app logs data from your job and lets you access the real time figures from your REFMATE via Bluetooth connection. Log maintenance activities and be ahead of the game with constant updates.

Access Control Valves

3431024: 1/4 x 1/4

3431025: 1/4 x 5/16 R410a

3431026: 5/16 x 5/16 R410a



Self-closing valves for peace of mind

A modular system with exchangeable connections

Manufactured in Switzerland for premium quality

HY-TELL Hydraulic Pipe Bender

8036000



Suitable for a broad range of pipe, including
1/4", 5/16", 3/8", 1/2", 5/8", 3/4" or 7/8" diameters

Sturdy placement provides bending angle assistance

Durable carry case for easy transportation

HY-EX Expander Tool Kit

8001930



6 expander heads that cover imperial-sized tubes of 3/8", 1/2" 5/8", 3/4", 7/8" and 1 1/8" diameters

One-handed operation with quick release for continuous and convenient expansion

Compact design to fit into hard to reach places, with an ergonomic 120° handling angle

TAP Wireless Digital Pressure and Temperature Gauge Set

8054072



The wireless K-type temperature clamp works on pipe diameters from 1/4" to 1 5/8" (6mm - 42mm)

Stores over 50 common refrigerants, or upload more via microUSB

Connect up to 6 pressure gauges and temperature clamps

LP-88 Infrared Thermometer

8001499



Easy to use with a built in 8 point laser for accurate measurement

A wide temperature range of -60°C to 550°C

Practical pistol grip and 180g light weight for comfortable use

REF-VAC Vacuum Gauge

8001980



Continuous reading during evacuation process,
with an accuracy of +/-10%

Read measurements in pascal, microns, mbar,
Torr, mTorr, psi and inHg

Easily see changing data with large LCD screen

Valve Core Replacing Tool

3431027: 32525- 1/4

3431028: 32525- 5/16



Evacuate and charge without losing refrigerant
and while under pressure

Deep vacuum measuring system

360° swivel connection

OCTA-Wireless Scale

8001786



Wireless keypad can be easily programmed
or recalibrated as needed

110kg capacity with a 10 meter signal range

60 hour battery life for both remote control and platform

Shop online with maX



Shop easily online through the maX app using the product codes, or visit your nearest ACTROL store.

Download maX on:



actrol.com.au